



Product No. MOHP20



HP LA2006x Black 20" 5ms Pivot, Swivel & Height Adjustable Widescreen LCD Monitor 250 cd/m2 1000:1

Product Descriptions

Introducing a slim, modern LED backlit monitor that helps improve recyclability and durability, while a slider stand helps enhance comfort adjustability.

The HP Compaq LA2006x possesses a modern design that is sure to impress. The sculpted, soft black, slender form almost vanishes into the background so you can focus on the vibrant images displayed on the widescreen LED backlit panel.

Product Details

Although care has been taken to ensure the accuracy of the information provided in this Product Specification, CTR is in no way liable for any errors, omissions or changes in specifications.

Features

FORWARD-LOOKING DESIGN

- ❖ A slider stand with an extensive height adjustability range of 130mm means the monitor head can be lifted high to better reach taller users' eyes. It can also adjust low to the desk to help reach the eyes of students as well as the aging workforce, who may wear multi-focal lenses.
- ❖ 35° of tilt adjustability helps provide clear views at many different angles.
- ❖ 90° pivot rotation makes longer text easy to read with less scrolling
- ❖ Swivel makes sharing your screen with others as simple as a quick turn of the head o VGA, DVI-D, and DisplayPort inputs provide a wide range of advanced connectivity options
- ❖ A built-in two port USB hub puts flash stick data close at hand
- ❖ A Cable management clip keeps unruly lines in place
- ❖ VESA compatibility provides a wide range of mounting solutions

FORWARD-THINKING TECHNOLOGY

HP strives to make a positive impact on business. Because of this, the LA2006x is EPEAT Gold registered, ENERGY STAR qualified, and TCO Displays certified. Additional features include:

- ❖ A 1M:1 DCR, a 170° wide viewing angle, and fast 5ms response times for precise views2
- ❖ Display Assistant for custom picture quality, theft deterrence, and energy savings enablement

Specifications

Part number	XN374A
Panel type	TN w/ LED backlight
Viewable image area	50,8 cm (20 in) widescreen; diagonally measured
Viewing angle	Up to 170° horizontal/160° vertical (10:1 minimum contrast ratio)
Brightness	250 nits (cd/m2)
Contrast ratio	1000:1 (typical); 1,000,000:1 (dynamic)
Response rate	5 ms (on/off)
Frequency	Horizontal: 24 to 83 kHz; Vertical: 50 to 76 Hz
Native resolution	1600 x 900 @ 60 Hz
Input signal	VGA, DVI-D (w/HDCP support), DisplayPort
Input power	100 – 240 VAC, 50/60 Hz
Weight	5,48 kg (12.1 lb)
Environmental	Operating: 5° to 35° C (41° to 95° F)
Power consumption	Maximum: 34 watts; Typical: 26 watts

Head Office Location

