

Product No. VISTHD



HDMI Over Cat5 / Cat6 Extender with IR - 100 ft (30m)

Power Free

Product Details

Although care has been taken to ensure the accuracy of the information provided in this Product Specification, CTR is in no way liable for any errors, omissions or changes in specifications.

Features

Cost-effective HDMI extension through nonproprietary network cabling

The ST121SHD30 HDMI over CAT5e/CAT6 Video Extender kit lets you extend HDMI audio/ video and an IR remote control signal by up to 100 feet (30 Meters) over dual Cat5e or Cat6 cable. For added versatility this HDMI extender kit is powered via the HDMI bus, and does not require any additional power adapter.

Clean, professional installation

With support for High-Definition resolutions of up to 1920x1080/ 1080p and the accompanying digital audio, this cost-effective HD extender can easily be installed using new or existing Ethernet infrastructure wiring.

Built in mounting hardware, and no power adapters required

Because the extender kit does not require a power adapter, you can easily extend an HDMI signal in areas where access to power outlets is limited.

Product Descriptions

The ST121SHD30 HDMI® over CAT5e/CAT6 Video Extender kit lets you extend HDMI audio/video and an IR remote control signal by up to 100 feet (30 Meters) over dual Cat5e or Cat6 cable. For added versatility this HDMI extender kit is powered via the HDMI bus, and does not require any additional power adapter.

With support for High-Definition resolutions of up to 1920x1080 / 1080p and the accompanying digital audio, this cost-effective HD extender can easily be installed using new or existing Ethernet infrastructure wiring. Plus, because the extender kit does not require a power adapter, you can easily extend an HDMI signal in areas where access to power outlets is limited.

Specifications	
Cabling	Cat 5 UTP or better
Daisy-Chain	No
Ports	1
General Specifications	IR dongle frequency - 35 to 56 khz
Max Distance	30 m / 100 ft
Maximum Digital Resolutions	1080p / 1920x1080
Wide Screen Supported	Yes
Local Unit Connectors	1 - HDMI (19 pin) Female
	2 - RJ-45 Female
Remote Unit Connectors	1 - HDMI (19 pin) Female
	2 - RJ-45 Female
Humidity	0% - 80 %
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-10°C to 60°C (14°F to 115°F)
Product Weight	8.3 oz [235 g]
Product Length	3.2 in [82 mm]
Product Height	0.9 in [22 mm]
Enclosure Type	Aluminum

